

GZM3200KM

Entry-level Roll-To-Roll LED UV printer!




- ◆ Up to 8 Konica 1024i/1024a high-speed print heads.
- ◆ Dual water cooling LED UV lamps are effective and energy saving.
- ◆ Negative pressure system assures stable ink supply and nozzle jetting.
- Optional white ink enables printing on more kinds of materials such as transparent media and color media.
- ◆ White ink stirring system prevents print head clogging & enables stable printing.
- ◆ Dual air shafts and dual dancer bars ensure steady and accurate media delivery, especially for soft media.
- ◆ Panasonic A6 400W servo system assures smooth, stable & accurate carriage movement.
- ◆ Huge back light panel for easy checking the output quality right after printing, increasing the productivity.

ITEM	SPECIFICATION			
Model	GZM3200KM			
Print Head	4~8 Konica 1024i/Konica 1024a print heads			
Head Config.	1XKCMY 2XKCMY 1XKCMY+W			
Curing System	LED UV curing system			
Ink	UV curable ink			
Colors	Standard: KCMY, Optional: W			
Ink Supply System	Negative pressure system + White ink stirring system			
Cleaning System	Positive Purging System			
Servo System	Panasonic A6 400W servo system			
Media System	2 air shafts + 2 dancer bars + pinch rollers			
Media Type	Backlit, Banner, Canvas, Backlit Film, Reflective Film, Tarpaulin, Backlit Textile, Vinyl, Wall coverings, PP, PET.			
Media Width	Max. 3200mm			
Printing Width	Max. 3200mm			
Printing Speed	Konica 1024a	Resolution	1 group head	2 groups heads
	Draft Production Quality Hi-Precision	480X1080dpi 480X1440dpi 480X1080dpi 480X1440dpi	39m²/h 31m²/h 21m²/h 15.2m²/h	72m²/h 58m²/h 40m²/h 30m²/h
	Konica 1024i	Resolution	1 group head	2 groups heads
	Draft Production Quality Hi-Precision	540X1080dpi 540X1440dpi 540X1080dpi 540X1440dpi	36.5m²/h 28.6m²/h 19.4m²/h 14.4m²/h	67.5m²/h 53.5m²/h 37m²/h 28.5m²/h
Data Interface	External: USB2.0; Internal: SCSI cable			
Working Environment	Temperature: 20°C~28°C, Humidity: 40%~70%			
Software	PhotoPRINT UV Edition (Optional Onyx)+GZ Printer Manager			
Image Format	Bitmap, TIF, Quark Xpress, JPEG, EPS, PDF			
Power	Single-phase, 50/60Hz, AC220V±10%, 10A, Regulator: 10kVA			
Dimension	4790x1193x1520mm(Installed)/5930x1150x1740mm(Packed)			
Weight(N.W./G.W.)	1035kgs/1335kgs			

^{*}Specifications are liable to change without prior notice.

Main Features



Konica 1024i/1024a print heads



Negative Pressure System



LED UV lamp & Anti-collision unit



Air Shaft and dancer bar



Panasonic A6 400W servo system



Huge LED back light panel

نشانی: تهران بزرگراه جلال آل احمد، غرب پل آزمایش ساختمان صنعت، پلاک ۲۷۹ طبقه سوم تلفن: ۹۱۲۸۳۷۹۲۲ همراه: ۹۹۲۲۹۳۷۹۲۲ همراه: ۹۹۲۲۹۹۲۲۹۰ نشانی کارخانه: اتوبان قم، حسن آباد، شهرک صنعتی شمس آباد، بلوار نارنجستان، گلبرگ ۹، پلاک ۸





(C) chap.record

